


JAN 20 1959

NBS

TECHNICAL NOTE

474

Critically Evaluated Transition Probabilities for Ba I and II



**U.S. DEPARTMENT OF COMMERCE
National Bureau of Standards**

NATIONAL BUREAU OF STANDARDS

The National Bureau of Standards¹ was established by an act of Congress March 3, 1901. Today, in addition to serving as the Nation's central measurement laboratory, the Bureau is a principal focal point in the Federal Government for assuring maximum application of the physical and engineering sciences to the advancement of technology in industry and commerce. To this end the Bureau conducts research and provides central national services in three broad program areas and provides central national services in a fourth. These are: (1) basic measurements and standards, (2) materials measurements and standards, (3) technological measurements and standards, and (4) transfer of technology.

The Bureau comprises the Institute for Basic Standards, the Institute for Materials Research, the Institute for Applied Technology, and the Center for Radiation Research.

THE INSTITUTE FOR BASIC STANDARDS provides the central basis within the United States of a complete and consistent system of physical measurement, coordinates that system with the measurement systems of other nations, and furnishes essential services leading to accurate and uniform physical measurements throughout the Nation's scientific community, industry, and commerce. The Institute consists of an Office of Standard Reference Data and a group of divisions organized by the following areas of science and engineering:

Applied Mathematics—Electricity—Metrology—Mechanics—Heat—Atomic Physics—Cryogenics²—Radio Physics²—Radio Engineering²—Astrophysics²—Time and Frequency.²

THE INSTITUTE FOR MATERIALS RESEARCH conducts materials research leading to methods, standards of measurement, and data needed by industry, commerce, educational institutions, and government. The Institute also provides advisory and research services to other government agencies. The Institute consists of an Office of Standard Reference Materials and a group of divisions organized by the following areas of materials research:

Analytical Chemistry—Polymers—Metallurgy—Inorganic Materials—Physical Chemistry.

THE INSTITUTE FOR APPLIED TECHNOLOGY provides for the creation of appropriate opportunities for the use and application of technology within the Federal Government and within the civilian sector of American industry. The primary functions of the Institute may be broadly classified as programs relating to technological measurements and standards and techniques for the transfer of technology. The Institute consists of a Clearinghouse for Scientific and Technical Information,³ a Center for Computer Sciences and Technology, and a group of technical divisions and offices organized by the following fields of technology:

Building Research—Electronic Instrumentation—Technical Analysis—Product Evaluation—Invention and Innovation—Weights and Measures—Engineering Standards—Vehicle Systems Research.

THE CENTER FOR RADIATION RESEARCH engages in research, measurement, and application of radiation to the solution of Bureau mission problems and the problems of other agencies and institutions. The Center for Radiation Research consists of the following divisions:

Reactor Radiation—Linac Radiation—Applied Radiation—Nuclear Radiation.

¹ Headquarters and Laboratories at Gaithersburg, Maryland, unless otherwise noted; mailing address Washington, D. C. 20234.

² Located at Boulder, Colorado 80302.

³ Located at 5285 Port Royal Road, Springfield, Virginia 22151.

UNITED STATES DEPARTMENT OF COMMERCE
C. R. Smith, Secretary
NATIONAL BUREAU OF STANDARDS • A. V. Astin, Director




TECHNICAL NOTE 474

ISSUED JANUARY 1969

Critically Evaluated Transition Probabilities for Ba I and II

B. M. Miles and W. L. Wiese
Atomic Physics Division
Institute for Basic Standards
National Bureau of Standards
Washington, D.C. 20234

NBS Technical Notes are designed to supplement the Bureau's regular publications program. They provide a means for making available scientific data that are of transient or limited interest. Technical Notes may be listed or referred to in the open literature.



Critically Evaluated Transition Probabilities

for Ba I and II^{*}

B. M. Miles and W. L. Wiese

Critically evaluated transition probabilities, in order of increasing quantum numbers, are compiled for Ba I and II from available literature sources.

Key words: Ba I, Ba II, line strengths, oscillator strengths, transition probabilities

This special compilation of critically evaluated transition probabilities of Ba I and II has been carried out in response to much recent interest in the barium spectrum. We have for the arrangement of these tables adopted the same format as used in our general compilations of atomic transition probabilities for the first¹ and second ten elements.² Thus we follow in our coding exactly the notation used in the other compilations. For convenience, we have collected below the special notation used in the evaluation of these two spectra.

Special Notation used in the Tables:

1. Multiplet column:

Numbers in parenthesis are the multiplet numbers of Ref. 3 and 4.

2. Wavelength column:

Wavelengths in brackets are calculated wavelengths rather than observed ones.

* Research supported by the Advanced Research Projects Agency of the Department of Defense under the Strategic Technology Office.

3. Accuracy column:

- B - for uncertainties within 10%
- C - for uncertainties within 25%
- D - for uncertainties within 50%
- E - for uncertainties larger than 50%.

4. Literature column:

- n - indicates the values have been normalized to a basis which is different from the one chosen by the author.
- ls - relative values obtained from LS-coupling tables.

REFERENCES

- [1] Wiese, W.L., Smith, M.W., and Glennon, B.M., "Atomic Transition Probabilities-Hydrogen through Neon", NSRDS-NBS 4 Vol. 1 (1966) (U.S. Government Printing Office, Washington, D.C.).
- [2] Wiese, W.L., Smith, M.W., and Miles, B.M., "Atomic Transition Probabilities-Sodium through Calcium", NSRDS-NBS 22 Vol. 2 to be published (U.S. Government Printing Office, Washington, D.C.).
- [3] Moore, C.E., "A Multiplet Table of Astrophysical Interest Revised Edition," National Bureau of Standards Tech. Note 36 (1959) (U.S. Government Printing Office, Washington, D.C.).
- [4] Moore, C.E., "An Ultraviolet Multiplet Table," National Bureau of Standards Circular 488, Sec. 3 (1962) (U.S. Government Printing Office, Washington, D.C.).

BARIUM I

Ba I

Ground State

$4s^2 4p^6 4d^{10} 5s^2 5p^6 6s^2 \ ^1S_0$

Ionization Potential

5.210 eV = 42032.4 cm⁻¹

Allowed Transitions

List of tabulated lines:

Wave length [Å]	No.	Wave length [Å]	No.	Wave length [Å]	No.
2409.98	36	4323.00	44	5971.70	6
2414.83	35	4325.15	40	5997.09	6
2420.85	34	4332.91	44	6019.47	6
2428.17	33	4350.33	38	6063.12	6
2433.28	25	4402.54	41	6110.78	6
2439.55	32	4406.85	40	6341.68	5
2445.38	24	4431.89	38	6450.85	5
2453.12	31	4467.09	39	6482.91	9
2473.20	30	4488.98	44	6498.76	5
2500.2	29	4493.64	44	6527.31	5
2543.2	28	4505.92	38	6595.33	5
2596.64	22	4523.17	38	6675.27	5
2646.50	27	4573.85	38	6693.84	5
2702.63	21	4579.64	41	6865.69	8
2739.24	20	4591.82	13	7059.94	3
2785.28	26	4599.75	37	7120.33	4
3071.58	23	4604.98	13	7195.24	43
3501.11	17	4619.92	45	7280.30	3
3889.33	16	4628.33	13	7392.41	43
3909.91	1	4673.62	13	7417.53	4
3935.72	1	4691.62	38	7488.08	3
3937.87	1	4700.43	45	7672.09	3
3993.40	1	4726.44	14	7780.48	3
3995.66	1	5535.48	19	7905.75	43
4132.43	15	5777.62	42	7911.38	18
4239.56	46	5800.23	42	15000	11
4242.61	40	5805.69	7	27751	12
4264.42	44	5826.30	10	29224	12
4283.10	2	5907.64	6		

Aside from the principal resonance line and several other lines of the resonance series, the oscillator strength situation for Ba I is quite poor and needs drastic improvement.


The adopted value for the principal resonance line is based on the lifetime measurements of the $6s6p\ ^1P_1$ state by Swagel and Lurio [1] with the Hanle-effect method ($\tau = 8.37$ nsec) and by Hulpke, Paul and Paul [2] with the phase-shift technique ($\tau = 8.36$ nsec). For converting this number to a transition probability, the small contribution of the $6s5d\ ^1D_2 - 6s6p\ ^1P_1$ transition has to be considered, for which only a rough estimate is available from a Stark effect measurement by Paul (see Ref. [2]). The "hook measurements" of Prokof'ev [3] as well as Ostrovskii and Penkin [4] and the semi-empirical calculations by Vainshtein and Poluektov [5] have been employed for obtaining a relative f-value for the intercombination line $6s^2\ ^1S_0 - 6s6p\ ^3P_1$. This number should also be fairly accurate since the three determinations agree within 16 percent. We have furthermore deduced the f-values for the infrared $6s5d\ ^3D_{1,2} - 6s6p\ ^3P_1$ transitions from the lifetime measurement of Bucka and Nagel [6] for the $6s6p\ ^3P_1$ state by applying the above determined value for the intercombination line and by using the LS-coupling ratios.

The transitions of the resonance series $6s^2\ ^1S - 6snp\ ^1P$ have been studied by Penkin and Shabanova [7] for the levels $n=6$ up to $n=18$ by employing the "hook" method. The authors find a highly irregular series behavior which is graphically presented in Figure 1. Most likely, perturbations of the upper states by other neighboring $1P$ states are responsible for this. The accuracy of their results, which are normalized for the principal resonance line against the above mentioned lifetime, is estimated to be within 50 percent.

Various other transitions have been studied by Ostrovskii and Penkin [4] with the "hook" method, and by Eicke [8] with a vortex-stabilized arc. Also, Warner [9] has calculated the f-values of a few ns-mp transitions with the scaled Thomas-Fermi method, accounting for configuration mixing effects.

Ostrovskii and Penkin's numbers are relative f-values, which we have normalized against the resonance line using the earlier discussed accurate lifetime results. Eicke obtains absolute f-values, but they cannot be directly linked to the resonance line which he has not measured.

The results of the three authors differ greatly, often by factors of two and much more. We have therefore performed some extensive analyses to search for causes of the discrepancies. For example, we have plotted the ratios of Eicke's f-values against Ostrovskii and Penkin's f-values as a function of upper and lower energy levels as well as wavelengths. None of these have revealed any clear systematic trends, however, we noticed that there may be some indication of a systematic dependence in Eicke's values. Namely, his f-values become drastically smaller relative to the "hook" results for some of the lines involving very high upper energy levels. In the Ostrovskii and Penkin experiment, on the other hand, only the populations of the lower energy levels come into play and



for these no apparent trend could be noticed. Furthermore, the greatest uncertainties in Eicke's method lie in finding the absolute scale while his relative values should be much more accurate. We find indeed that a shift of his absolute scale by enlarging all his values by about a factor of two would bring at least half of his f-values into a 50 percent agreement with Ostrovskii and Penkin's normalized values. We have finally adopted Ostrovskii and Penkin's data because of the following main reasons:

- a) These data may be directly linked up with the precise life-time results for the resonance line.
- b) The "hook" method is a time proven method, which has in many other instances given reliable results, while the method used by Eicke has been only applied in two other experiments. (However, it must be stated that in at least one of the other two experiments, which we have analyzed in detail, Eicke's method gives reliable results.)
- c) Uncertainties in the temperature measurement should be somewhat less critical for Ostrovskii and Penkin's experiment than for Eicke's experiment.
- d) The few calculated data do not appear to be too trustworthy, either, since they do not even agree well with experiment on a relative scale, for which the measurements should be fairly accurate.

Since we expect that temperature errors will be quite sensitive even in the adopted Ostrovskii and Penkin experiment, we estimate the overall uncertainties not to be much below 50 percent, but even this figure cannot be considered as too well established because of the presently existing discrepancies.

References

- [1] Swagel, M.W. and Lurio, A., Phys. Rev. 169, 114-119 (1968).
- [2] Hulpke, E., Paul, E. and Paul, W., Z. Physik 177, 257-268 (1964).
- [3] Prokof'ev, V.K., Zhur. Eksptl. i. Teoret. Fiz. 1, 111-122 (1931).
- [4] Ostrovskii, Yu. I. and Penkin, N.P., Optics and Spectroscopy (U.S.S.R.) 9, 371-373 (1960).
- [5] Vainshtein, L.A. and Poluektov, I.A., Optics and Spectroscopy (U.S.S.R.) 12, 254-257 (1962).
- [6] Bucka, H. and Nagel, H.H., Ann. Physik 8, 329-332 (1961).
- [7] Penkin, N.P. and Shabanova, L.N., Optics and Spectroscopy (U.S.S.R.) 12, 1-5 (1962).
- [8] Eicke, H.F., Z. Physik 168, 227-238 (1962).
- [9] Warner, B., Monthly Notices Roy. Astron. Soc. 140, 55-59 (1968).

No.	Transition Array	Multiplet	$\lambda(\text{\AA})$	$E_i(\text{cm}^{-1})$	$E_k(\text{cm}^{-1})$	g_i	g_k	$A_{ki}(10^8 \text{s}^{-1})$	f_{ik}	S(at.u.)	log gf	Accu.	L
1	6s5d - 6s(² S)4f	³ D - ³ F° (8)	3993.40 3935.72 3909.91 3995.66 3937.87	9596.55 9215.52 9033.99 9596.55 9215.52	34630.8 34616.7 34602.8 34616.7 34602.8	7 5 3 7 5	9 7 5 7 5	0.55 0.47 0.49 0.088 0.11	0.17 0.15 0.19 0.021 0.025	16 9.9 7.3 1.9 1.6	0.08 -0.12 -0.25 -0.83 -0.90	D D D D D	4n 4n 4n 4n 4n
2		¹ D - ¹ F°	4283.10	11395.4	34736.4	5	7	0.64	0.25	17	0.09	D	4n
3	6s5d - 5d(² S)6p'	³ D - ³ F° (5)	7059.94 7280.30 7672.09 7488.08 7780.48	9596.55 9215.52 9033.99 9596.55 9215.52	23757.1 22947.4 22064.7 22947.4 22064.7	7 5 3 7 5	9 7 5 7 5	0.71 0.53 0.31 0.10 0.13	0.68 0.59 0.45 0.084 0.12	110 70 34 14 15	0.68 0.47 0.14 -0.23 -0.23	D D D D D	4n 4n 4n 4n 4n
4		³ D - ¹ D	7120.33 7417.53	9033.99 9596.55	23074.4 23074.4	3 7	5 5	0.21 0.025	0.27 0.015	19 2.5	-0.10 -0.98	D D	4n 4n
5		³ D - ³ D° (6)	6527.4 6498.76 6527.31 6595.33 6693.84 6675.27 6341.68 6450.85	9357.02 9596.55 9215.52 9033.99 9596.55 9215.52 9215.52 9033.99	24672.9 24979.9 24531.5 24192.1 24531.5 24192.1 24979.9 24531.5	15 7 5 3 7 5 5 3	15 7 5 3 5 3 7 5	1.0 0.86 0.59 0.72 0.28 0.35 0.19 0.11	0.66 0.55 0.38 0.47 0.14 0.14 0.16 0.11	210 82 40 31 21 15 16 7.3	0.99 0.58 0.27 0.15 -0.02 -0.15 -0.11 -0.47	D D D D D D D D	4n 4n 4n 4n 4n 4n 4n 4n

No.	Transition Array	Multiplet	$\lambda(\text{\AA})$	$E_i(\text{cm}^{-1})$	$E_k(\text{cm}^{-1})$	g_i	g_k	$A_{ki}(10^8 \text{s}^{-1})$	f_{ik}	S(at.u.)	log gf	Accu.	L
6		$3D - 3P^\circ$ (7)	6066.1	9357.02	25837.5	15	9	1.4	0.45	140	0.83	D	4n
			6110.78	9596.55	25956.5	7	5	1.0	0.40	56	0.44	D	4n
			6063.12	9215.52	25704.1	5	3	0.97	0.32	32	0.21	D	4n
			6019.47	9033.99	25642.2	3	1	1.4	0.26	16	-0.10	D	4n
			5971.70	9215.52	25956.5	5	5	0.29	0.15	15	-0.11	D	4n
			5997.09	9033.99	25704.1	3	3	0.46	0.25	15	-0.12	D	4n
			5907.64	9033.99	25956.5	3	5	0.036	0.031	1.8	-1.03	D	4n
7		$3D - 1F^\circ$	5805.69	9596.55	26816.3	7	7	0.040	0.020	2.7	-0.85	D	4n
8		$1D - 3P^\circ$	6865.69	11395.4	25956.5	5	5	0.078	0.055	6.2	-0.56	D	4n
9		$1D - 1F^\circ$	6482.91	11395.4	26816.3	5	7	0.44	0.39	42	0.29	D	4n
10		$1D - 1P^\circ$	5826.30	11395.4	28554.3	5	3	0.97	0.30	28	0.17	D	4n
11	6s5d - 6s(2S)6p	$1D - 1P^\circ$	15000	11395.4	18080.3	5	3	0.049	0.10	25	-0.30	E	2
12		$3D - 3P^\circ$	29224	9215.52	12636.6	5	3	0.00342	0.0263	12.7	-0.88	C	6, ℓ_s
			27751	9033.99	12636.6	3	3	0.00133	0.0154	4.22	-1.335	C	6, ℓ_s
13	6p5d - 6s(2S)7p	$3D - 3P^\circ$	4673.62	9596.6	30987.3	7	5	0.065	0.0015	1.6	-0.97	D	4n
			4628.33	9215.52	30815.6	5	3	0.060	0.012	0.88	-1.24	D	4n
			4604.98	9033.99	30743.5	3	1	0.077	0.0082	0.37	-1.61	D	4n
			4591.82	9215.52	30987.3	5	5	0.016	0.0052	0.39	-1.59	D	4n
14		$1D - 1P^\circ$	4726.44	11395.4	32547.1	5	3	0.69	0.14	11	-0.16	D	4n
15	6s 2 - 5d(2S)6p'	$1S - 3D^\circ$	4132.43	0.00	24192.1	1	3	0.013	0.0099	0.13	-2.00	D	4n, 7n

No.	Transition Array	Multiplet	$\lambda(\text{\AA})$	$E_i(\text{cm}^{-1})$	$E_k(\text{cm}^{-1})$	g_i	g_k	$A_{ki}(10^8 \text{s}^{-1})$	f_{ik}	S(at.u.)	log gf	Accu.	L
16		$1s - 3p^\circ$	3889.33	0.00	25704.1	1	3	0.015	0.010	0.13	-1.99	D	4n,7n
17		$1s - 1p^\circ$ (3)	3501.11	0.00	28554.3	1	3	0.29	0.16	1.9	-0.79	D	7n
18	$6s^2 - 6s(^2S)6p$	$1s - 3p^\circ$ (1)	7911.38	0.00	12636.6	1	3	0.00353	0.00994	0.259	-2.00	C+	3,4,5
19		$1s - 1p^\circ$ (2)	5535.48	0.00	18080.3	1	3	1.15	1.59	29.0	0.201	B	1,2
20	$6s^2 - 5d(^2S)7p'$	$1s - 3d^\circ$	2739.24	0.00	36495.8	1	3	0.0091	0.0031	0.028	-2.51	D	7n
21		$1s - 3p^\circ$	2702.63	0.00	36990.0	1	3	0.025	0.0081	0.072	-2.09	D	7n
22		$1s - 1p^\circ$	2596.64	0.00	38499.9	1	3	0.12	0.035	0.30	-1.45	D	7n
23	$6s^2 - 6s(^2S)7p$	$1s - 1p^\circ$ (4)	3071.58	0.00	32547.1	1	3	0.41	0.17	1.7	-0.76	D	7n
24	$6s^2 - 5d(^2S)8p'$	$1s - 3d$	2445.38	0.00	40893.4	1	3	0.0057	0.0015	0.012	-2.81	D	7n
25		$1s - 3p$	2433.28	0.00	41096.8	1	3	0.0095	0.0025	0.020	-2.60	D	7n
26	$6s^2 - 6s(^2S)8p$	$1s - 1p^\circ$	2785.28	0.00	35892.5	1	3	0.028	0.0099	0.090	-2.01	D	7n
27	$6s^2 - 6s(^2S)9p$	$1s - 1p^\circ$	2646.50	0.00	37774.5	1	3	0.011	0.0035	0.031	-2.45	D	7n
28	$6s^2 - 6s(^2S)10p$	$1s - 1p^\circ$	2543.2	0.00	39308.7	1	3	0.041	0.012	0.099	-1.93	D	7n
29	$6s^2 - 6s(^2S)11p$	$1s - 1p^\circ$	2500.2	0.00	39984.8	1	3	0.015	0.0043	0.035	-2.37	D	7n
30	$6s^2 - 6s(^2S)12p$	$1s - 1p^\circ$	2473.20	0.00	40421.23	1	3	0.0057	0.0016	0.013	-2.81	D	7n
31	$6s^2 - 6s(^2S)13p$	$1s - 1p^\circ$	2453.12	0.00	40764.4	1	3	6.4×10^{-4}	1.7×10^{-4}	0.0014	-3.76	D	7n
32	$6s^2 - 6s(^2S)14p$	$1s - 1p^\circ$	2439.55	0.00	40991.2	1	3	0.0012	3.3×10^{-4}	0.0027	-3.48	D	7n
33	$6s^2 - 6s(^2S)15p$	$1s - 1p^\circ$	2428.17	0.00	41183.3	1	3	0.0078	0.0021	0.017	-2.68	D	7n

No.	Transition Array	Multiplet	$\lambda(\text{\AA})$	$E_i(\text{cm}^{-1})$	$E_k(\text{cm}^{-1})$	g_i	g_k	$A_{ki}(10^8 \text{s}^{-1})$	f_{ik}	S(at.u.)	log gf	Accu.	L
34	$6s^2 - 6s(^2S)16p$	$1s - 1p^\circ$	2420.85	0.00	41307.8	1	3	0.0025	6.7×10^{-4}	0.0053	-3.18	D	7n
35	$6s^2 - 6s(^2S)17p$	$1s - 1p^\circ$	2414.83	0.00	41410.8	1	3	0.0012	3.0×10^{-4}	0.0024	-3.52	D	7n
36	$6s^2 - 6s(^2S)18p$	$1s - 1p^\circ$	2409.98	0.00	41494.1	1	3	6.1×10^{-4}	1.6×10^{-4}	0.0013	-3.80	D	7n
37	$6s(^2S)6p - 6p^2$	$3p^\circ - 1s$	4599.75	12636.6	34370.8	3	1	1.0	0.11	4.8	-0.50	D	4n
38		$3p^\circ - 3p$	<u>4514.6</u>	<u>13083.3</u>	<u>35227.6</u>	9	9	2.5	0.77	100	0.84	D	4n
			4523.17	13514.7	35616.9	5	5	0.96	0.29	22	0.17	D	4n
			4505.92	12636.6	34823.4	3	3	1.1	0.32	14	-0.02	D	4n
			4691.62	13514.7	34823.4	5	3	1.6	0.33	25	0.21	D	4n
			4573.85	12636.6	34493.9	3	1	2.9	0.31	14	-0.04	D	4n
			4350.33	12636.6	35616.9	3	5	0.60	0.28	12	-0.07	D	4n
			4431.89	12266.0	34823.4	1	3	1.2	1.1	16	0.03	D	4n
39	$6s(^2S)6p - 5d(^2D)6d$	$3p^\circ - 3G$	4467.09	13514.7	35894.3	5	7	0.066	0.028	2.0	-0.86	D	4n
40		$3p^\circ - 3D$	4325.15	13514.7	36628.9	5	7	0.071	0.028	2.0	-0.86	D	4n
			4242.61	12636.6	36200.4	3	5	0.056	0.025	1.1	-1.12	D	4n
			4406.85	13514.7	36200.4	5	5	0.10	0.030	2.2	-0.83	D	4n
41		$3p - 1D$	4579.64	13514.7	35344.4	5	5	1.8	0.56	42	0.45	D	4n
			4402.54	12636.6	35344.4	3	5	0.70	0.34	15	0.01	D	4n
42	$6s6p - 6s(^2S)6d$	$3p - 3D$ (9)	5777.62	13514.7	30818.1	5	7	1.5	1.0	99	0.72	D	4n
			5800.23	13514.7	30750.7	5	5	0.48	0.24	23	0.08	D	4n
43	$6s6p - 6s(^2S)7s$	$3p^\circ - 3s$ (10)	<u>7644.9</u>	<u>13083.3</u>	26160.3	9	3	1.4	0.40	90	0.55	D	4n
			7905.75	13514.7	26160.3	5	3	0.63	0.35	46	0.25	D	4n
			7392.41	12636.6	26160.3	3	3	0.50	0.41	30	0.09	D	4n
			7195.24	12266.0	26160.3	1	3	0.24	0.56	13	-0.25	D	4n

No.	Transition Array	Multiplet	$\lambda(\text{\AA})$	$E_i(\text{cm}^{-1})$	$E_k(\text{cm}^{-1})$	g_i	g_k	$A_{ki}(10^8 \text{s}^{-1})$	f_{ik}	S(at.u.)	log gf	Accu.	L
44	6s6p - 6s(² S)7d	³ P° - ³ D	4488.98 4323.00 4264.42 4493.64 4332.91	13514.7 12636.6 12266.0 13514.7 12636.6	35785.3 35762.2 35709.3 35762.2 35709.3	5 3 1 5 3	7 5 3 5 3	0.42 0.15 0.15 0.36 0.15	0.18 0.072 0.13 0.11 0.043	13 3.1 1.8 8.1 1.9	-0.05 -0.67 -0.90 -0.26 -0.89	D D D D D	4n 4n 4n 4n 4n
45	6s6p - 6s(² S)8s	³ P° - ³ S	4619.92 4700.43	12266.0 12636.6	33905.3 33905.3	1 3	3 3	0.093 0.24	0.090 0.079	1.4 3.7	-1.05 -0.63	D D	4n 4n
46	6s6p - 6s(² S)9s	³ P° - ³ S	4239.56	13514.7	37095.5	5	3	0.24	0.038	2.7	-0.72	D	4n

BARIUM II

Ba II

Ground State

$4s^2 4p^6 4d^{10} 5s^2 5p^6 6s^2 S_{1/2}$

Ionization Potential

10.001 eV = 80686.87 cm⁻¹

Allowed Transitions

List of tabulated lines:

Wavelength [Å]	No.	Wavelength [Å]	No.	Wavelength [Å]	No.
1413.3	13	2200.9	25	4934.09	17
1417.2	12	2232.8	24	4997.81	41
1444.7	11	2235.4	24	5185.1	35
1461.3	11	2286.0	25	5361.35	31
1486.6	10	2528.40	22	5391.60	31
1503.9	10	2634.78	22	5413.6	2
1554.3	8	2641.37	22	5421.05	31
1572.7	8	2647.26	23	5428.79	2
1573.9	8	2771.35	23	5480.30	2
1630.4	19	3816.7	33	5784.18	38
1674.4	7	3842.8	33	5853.68	6
1694.3	7	3891.78	20	5981.25	38
1697.2	7	4024.1	4	5999.85	38
1761.7	9	4057.5	4	6135.83	39
1771.1	9	4130.65	20	6141.72	6
1787.0	9	4166.00	20	6363.2	16
1892.5	28	4287.80	43	6373.2	32
1904.16	5	4325.73	42	6378.91	39
1906.8	29	4329.62	42	6457.7	32
1924.77	5	4405.23	43	6496.90	6
1954.3	28	4470.7	3	7556.8	15
1955.1	28	4509.6	3	7678.3	15
1970.3	29	4524.93	21	8496.8	47
1985.7	26	4554.03	17	8591.4	1
1999.54	18	4616.04	42	8661.9	1
2009.3	27	4708.94	40	8703.7	47
2052.8	26	4843.46	40	8710.82	30
2054.1	26	4847.14	41	8719.1	47
2080.0	27	4850.84	40	8737.74	30
2153.9	24	4899.93	21	8760.6	1

Wavelength [\AA]	No.	Wavelength [\AA]	No.	Wavelength [\AA]	No.
8793.2	48	10768	45	11932	46
8897.5	30	10770	14	12475	37
9031.5	48	10994	14	13058	34
9603.3	36	11089	45	14211	34
10115	36	11127	45	18729	44
10213	36	11519	46	19643	44
10710	14	11577	37	19845	44

The most accurate f -values in this spectrum belong to the lines having the $6p\ ^2P$ levels as their upper states. Precise lifetime measurements of these states using the Hanle effect technique have been performed by Bucka et al. [1] and Gallagher [2], and are in close agreement. Bucka et al. obtain for the $6p\ ^2P_{3/2}$ level a lifetime of 7.0 ± 0.6 nsec, while Gallagher's result is 6.27 ± 0.25 nsec. We have utilized Gallagher's data exclusively, since he has also reduced the lifetime data to transition probabilities by measuring the relative strengths of all lines originating from the $6p\ ^2P$ upper levels, i.e., the branching ratios. For a number of vacuum uv lines and some visible transitions, von Specht [3] has determined moderately precise f -values - he estimates uncertainties of 35% - from emission measurements with a wall-stabilized arc operating in a barium-argon atmosphere. There is unfortunately no direct link between the data of von Specht and the presumably more accurate lifetime results of Gallagher. A somewhat indirect comparison via a few low current arc measurements by Kolesnikov and Slepchenko [4] gives the indication that von Specht's data may be somewhat high. However, Kolesnikov and Slepchenko's data cannot be considered very reliable since their f -values disagree quite badly with other results, even on a relative scale.

For many other lines of at least moderate strength we use the recent calculations by Warner [5]. Warner uses essentially the Coulomb approximation by Bates and Damgaard [6] with a modified potential and makes some allowance for configuration mixing and perturbation effects. Since Ba II is basically a one-electron spectrum this should be a reasonable approach if the jumping electron has a little interaction with the core. This is indeed indicated by the few available comparisons with the above mentioned experiments by Gallagher and von Specht, some of which are presented in Table I. It is seen that very pronounced differences exist for the $5d$ - $6p$ transitions, which is clearly non-Coulombic. The agreement becomes then increasingly better as the jumping electron gets further away from the core, and is already quite acceptable for the $6s$ - $6p$ transition. Some isolated cancellation seems to be apparent as indicated for example by the rather small theoretical gf -value for the $6s$ - $8p$ transition. We have therefore limited our tabulation of Warner's f -values to those transitions which are either in the visible or near infrared (λ smaller than $20,000\ \text{\AA}$) and which have gf -values larger than 10^{-3} .

Table I. Comparison of some Ba II f-values calculated by Warner on the basis of the Coulomb-approximation with experimental results by Gallagher (Hanle-effect) and von Specht (stabilized arc).

Transition	λ	Warner [5]	Gallagher [2]	v. Specht [3]
5d $^2D_{5/2}$ - 6p $^2P_{3/2}^\circ$	6141.72	0.12	0.14	-
$^2D_{3/2}$ - $^2P_{3/2}^\circ$	5853.68	0.017	0.025	-
$^2D_{3/2}$ - $^2P_{1/2}^\circ$	6496.90	0.087	0.105	-
5d $^2D_{3/2}$ - 8p $^2P_{3/2}^\circ$	1761.7	1.12×10^{-4}	-	1.8×10^{-4}
$^2D_{3/2}$ - $^2P_{1/2}^\circ$	1771.1	0.93×10^{-4}	-	7.9×10^{-4}
$^2D_{5/2}$ - $^2P_{3/2}^\circ$	1787.0	0.035×10^{-3}	-	1.4×10^{-3}
5d $^2D_{3/2}$ - 6f $^2F_{5/2}^\circ$	1674.4	0.38×10^{-6}	-	1.4×10^{-2}
$^2D_{5/2}$ - $^2F_{7/2}^\circ$	1694.3	0.096×10^{-2}	-	1.2×10^{-2}
$^2D_{5/2}$ - $^2F_{5/2}^\circ$	1697.2	0.26×10^{-4}	-	7.3×10^{-4}
5d $^2D_{3/2}$ - 7f $^2F_{5/2}^\circ$	1554.3	0.45×10^{-2}	-	1.4×10^{-2}
$^2D_{5/2}$ - $^2F_{7/2}^\circ$	1572.7	0.22×10^{-2}	-	1.2×10^{-2}
$^2D_{5/2}$ - $^2F_{5/2}^\circ$	1573.9	2.95×10^{-4}	-	5.8×10^{-4}
6s $^2S_{1/2}$ - 6p $^2P_{3/2}^\circ$	4554.03	0.78	0.74	
$^2S_{1/2}$ - $^2P_{1/2}^\circ$	4934.09	0.37	0.35	-
6s $^2S_{1/2}$ - 8p $^2P_{1/2}^\circ$	1630.4	0.018×10^{-4}	-	6.6×10^{-4}
6p $^2P_{3/2}^\circ$ - 6d $^2D_{5/2}$	4130.65	0.898	-	1.2
$^2P_{3/2}^\circ$ - $^2D_{3/2}$	4166.00	0.103	-	0.095
6p $^2P_{1/2}^\circ$ - 7s $^2S_{1/2}$	4524.93	0.145	-	0.22

References

- [1] Bucka, H., Eichler, J. and Oppen, G., Z. Naturforsch. 21a, 654-656 (1966).
- [2] Gallagher, A., Phys. Rev. 157, 24-30 (1967).
- [3] von Specht, J., Max-Planck-Institut. für Physik und Astrophysik, MPI-PAE 4/68 (1968).
- [4] Kolesnikov, N.S. and Slepchenko, N.S., Fiz. Probl. Spektroskopii, Akad. Nauk. S.S.S.R., Materialy 13-Go (Trinadtsatogo) Soveshch., Leningrad 41-43 (1962).
- [5] Warner, B., Monthly Notices Roy. Astron. Soc. 139, 115-128 (1968).
- [6] Bates, D.R. and Damgaard, A., Phil. Trans. Roy. Soc. London, Ser. A 242, 101-122 (1949).

No.	Transition Array	Multiplet	$\lambda(\text{\AA})$	$E_i(\text{cm}^{-1})$	$E_k(\text{cm}^{-1})$	g_i	g_k	$A_{ki}(10^8 \text{ s}^{-1})$	f_{ik}	S(at.u.)	log gf	Accu.	L
1	4f - (¹ S)7d	$2^{\circ}\text{F}^{\circ} - 2^{\circ}\text{D}$	<u>8715.9</u> [8760.6] [8661.9] [8591.4]	<u>48387.0</u> 48483.3 48258.6 48258.6	<u>59857.1</u> 59895.0 59800.3 59895.0	14 8 6 6	10 6 4 6	0.035 0.031 0.038 0.0013	0.028 0.027 0.029 0.0015	11 6.2 4.9 0.25	-0.40 -0.67 -0.77 -2.06	D D D D	5 5 5 5
2	4f - (¹ S)8d	$2^{\circ}\text{F}^{\circ} - 2^{\circ}\text{D}$ (9)	<u>5457.7</u> 5480.30 5428.79 [5413.6]	<u>48387.0</u> 48483.3 48258.6 48258.6	<u>66704.8</u> 66725.4 66673.8 66725.4	14 8 6 6	10 6 4 6	0.020 0.018 0.023 8.4×10^{-4}	0.0065 0.0061 0.0067 3.7×10^{-4}	1.6 0.89 0.72 0.039	-1.04 -1.31 -1.40 -2.66	D D D D	5 5 5 5
3	4f - (¹ S)9d	$2^{\circ}\text{F}^{\circ} - 2^{\circ}\text{D}$	[4509.6] [4470.7]	48483.3 48258.6	70651.9 70620.4	8 6	6 4	0.012 0.014	0.0028 0.0028	0.33 0.25	-1.65 -1.77	D D	5 5
4	4f - (¹ S)10d	$2^{\circ}\text{F}^{\circ} - 2^{\circ}\text{D}$	[4057.5] [4024.1]	48483.3 48258.6	73122.2 73101.9	8 6	6 4	0.012 0.0053	0.0022 8.6×10^{-4}	0.23 0.068	-1.76 -2.29	D D	5 5
5	5d - (¹ S)5f	$2^{\circ}\text{D} - 2^{\circ}\text{F}^{\circ}$ (uv 4)	1924.77 1904.16	5674.82 4873.85	57631.6 57390.9	6 4	8 6	0.031 0.011	0.0023 8.6×10^{-4}	0.087 0.022	-1.86 -2.46	D D	3 3
6	5d - (¹ S)6p	$2^{\circ}\text{D} - 2^{\circ}\text{P}^{\circ}$ (2)	<u>6234.9</u> 6141.72 6496.90 5853.68	<u>5354.43</u> 5674.82 4873.85 4873.85	<u>21388.8</u> 219524 20261.6 21952.4	10 6 4 4	6 4 2 4	0.389 0.371 0.332 0.0487	0.136 0.14 0.105 0.025	27.9 17.0 8.98 1.93	0.134 -0.076 -0.377 -1.000	C+ C+ C+ C+	2 2 2 2
7	5d - (¹ S)6f	$2^{\circ}\text{D} - 2^{\circ}\text{F}^{\circ}$	<u>1686.4</u> [1694.3] [1674.4] [1697.2]	<u>5354.43</u> 5674.82 4873.85 5674.82	<u>64653.9</u> 64697.1 64596.3 64596.3	10 6 4 6	14 8 6 6	0.22 0.21 0.22 0.017	0.013 0.012 0.014 7.3×10^{-4}	0.73 0.40 0.31 0.024	-0.88 -1.14 -1.25 -2.36	D D D D	3 3 3 3

No.	Transition Array	Multiplet	$\lambda(\text{\AA})$	$E_i(\text{cm}^{-1})$	$E_k(\text{cm}^{-1})$	g_i	g_k	$A_{ki}(10^8 \text{ s}^{-1})$	f_{ik}	S(at.u.)	log gf	Accu.	L
8	5d - (¹ S)7f	² D - ² F°	<u>1565.3</u> [1572.7] [1554.3] [1573.9]	<u>5354.43</u> 5674.82 4873.85 5674.82	<u>69239.6</u> 69260.5 69211.7 69211.7	10 6 4 6	14 8 6 6	0.25 0.24 0.26 0.016	0.013 0.012 0.014 5.8x10 ⁻⁴	0.68 0.37 0.29 0.018	-0.88 -1.14 -1.25 -2.46	D D D D	3 3 3 3
9	5d - (¹ S)8p	² D - ² P°	<u>1779.9</u> [1787.0] [1771.1] [1761.7]	<u>5354.43</u> 5674.82 4873.85 4873.85	<u>61536</u> 61636 61336 61636	10 6 4 4	6 4 2 4	0.043 0.044 0.034 0.0039	0.0012 0.0014 7.9x10 ⁻⁴ 1.8x10 ⁻⁴	0.072 0.049 0.018 0.0042	-1.91 -2.08 -2.50 -3.14	D D D D	3 3 3 3
10	5d - (¹ S)8f	² D - ² F°	[1503.9] [1486.6]	5674.82 4873.85	72170.2 72142.7	6 4	8 6	0.15 0.14	0.0070 0.0070	0.21 0.14	-1.38 -1.55	D D	3 3
11	5d - (¹ S)9f	² D - ² F°	[1461.3] [1444.7]	5674.82 4873.85	74108.9 74091.0	6 4	8 6	0.087 0.081	0.0037 0.0038	0.11 0.072	-1.65 -1.82	D D	3 3
12	5d - (¹ S)10f	² D - ² F°	[1417.2]	4873.85	75438	4	6	0.038	0.0017	0.032	-2.17	D	3
13	5d - (¹ S)11f	² D - ² F°	[1413.3]	5674.82	76429	6	8	0.017	6.7x10 ⁻⁴	0.019	-2.40	D	3
14	5f - (¹ S)8d	² F° - ² D	<u>10895</u> [10994] [10770] [10710]	<u>57528.5</u> 57631.6 57390.9 57390.9	<u>66704.8</u> 66725.4 66673.8 66725.4	14 8 6 6	10 6 4 6	0.0017 0.0011 0.0024 1.3x10 ⁻⁴	0.0022 0.0015 0.0028 2.3x10 ⁻⁴	1.1 0.43 0.60 0.048	-1.52 -1.92 -1.77 -2.87	D D D D	5 5 5 5
15	5f - (¹ S)9d	² F° - ² D	[7678.3] [7556.8]	57631.6 57390.9	70651.9 70620.4	8 6	6 4	6.6x10 ⁻⁴ 0.0016	4.4x10 ⁻⁴ 9.3x10 ⁻⁴	0.089 0.14	-2.45 -2.25	D D	5 5
16	5f - (¹ S)10d	² F° - ² D	[6363.2]	57390.9	73101.9	6	4	0.0029	0.0012	0.15	-2.15	D	5

No.	Transition Array	Multiplet	$\lambda(\text{\AA})$	$E_1(\text{cm}^{-1})$	$E_k(\text{cm}^{-1})$	g_i	g_k	$A_{ki}(10^8 \text{s}^{-1})$	f_{ik}	S(at.u.)	log gf	Accu.	L
17	$6s - ({}^1S)6p$	$2S - 2P^\circ$ (1)	<u>4674.0</u> 4554.03 4934.09	0.00	21388.8	2	6	1.11	1.09	33.5	0.338	B	2
18	$6s - ({}^1S)7p$	$2S - 2P^\circ$ (uv 1)	1999.54	0.00	50011.2	2	4	0.10	0.012	0.16	-1.61	D	5
19	$6s - ({}^1S)8p$	$2S - 2P^\circ$	[1630.4]	0.00	61336	2	2	0.017	6.6×10^{-4}	0.0071	-2.88	D	3
20	$6p - ({}^1S)6d$	$2P^\circ - 2D$ (4)	4130.65 3891.78 4166.00	21952.4 20261.6 21952.4	46154.9 45949.5 45949.5	4 2 4	6 4 4	3.1 2.1 0.37	1.2 0.96 0.095	65 25 5.2	0.68 0.28 -0.42	D D D	3 5 3
21	$6p - ({}^1S)7s$	$2P^\circ - 2S$ (3)	4899.93 4524.93	21952.4 20261.6	42355.2 42355.2	4 2	2 2	1.2 0.72	0.21 0.22	13 6.6	-0.08 -0.36	D D	5 3
22	$6p - ({}^1S)7d$	$2P^\circ - 2D$ (uv 6)	<u>2598.8</u> 2634.78 2528.40 2641.37	<u>21388.8</u> 21952.4 20261.6 21952.4	<u>59857.1</u> 59895.0 59800.3 59800.3	6 4 2 4	10 6 4 4	0.79 0.76 0.71 0.12	0.13 0.12 0.14 0.012	6.8 4.1 2.3 0.43	-0.10 -0.32 -0.56 -1.30	D D D D	5 5 5 5
23	$6p - ({}^1S)8s$	$2P^\circ - 2S$ (uv 5)	<u>2728.7</u> 2771.35 2647.26	<u>21388.8</u> 21952.4 20261.6	58025.2 58025.2 58025.2	6 4 2	2 2 2	0.60 0.40 0.20	0.022 0.023 0.021	1.2 0.85 0.36	-0.87 -1.03 -1.39	D D D	5 5 5
24	$6p - ({}^1S)8d$	$2P^\circ - 2D$	<u>2206.0</u> [2232.8] [2153.9] [2235.4]	<u>21388.8</u> 21952.4 20261.6 21952.4	<u>66704.8</u> <u>66725.4</u> 66673.8 66673.8	6 4 2 4	10 6 4 4	0.40 0.29 0.53 0.044	0.049 0.033 0.074 0.0033	2.1 0.97 1.0 0.097	-0.53 -0.88 -0.83 -1.88	D D D D	5 5 5 5

No.	Transition Array	Multiplet	$\lambda(\text{\AA})$	$E_i(\text{cm}^{-1})$	$E_k(\text{cm}^{-1})$	g_i	g_k	$A_{ki}(10^8 \text{ s}^{-1})$	f_{ik}	S(at.u.)	log gf	Accu.	L
25	6p - (¹ S)9s	² P° - ² S	<u>2256.9</u> [2286.0] [2200.9]	<u>21388.8</u> 21952.4 20261.6	<u>65683.4</u> 65683.4 65683.4	6 4 2	2 2 2	0.32 0.13 0.20	0.0083 0.0052 0.014	0.37 0.16 0.21	-1.30 -1.68 -1.54	D D D	5 5 5
26	6p - (¹ S)9d	² P° - ² D	<u>2029.8</u> [2052.8] [1985.7] [2054.71]	<u>21388.8</u> 21952.4 20261.6 21952.4	<u>70639.3</u> 70651.9 70620.4 70620.4	6 4 2 4	10 6 4 4	0.23 0.20 0.25 0.029	0.024 0.019 0.030 0.0018	0.94 0.50 0.39 0.049	-0.85 -1.13 -1.22 -2.14	D D D D	5 5 5 5
27	6p - (¹ S)10s	² P° - ² S	<u>2055.9</u> [2080.0] [2009.3]	<u>21388.8</u> 21952.4 20261.6	<u>70014.7</u> 70014.7 70014.7	6 4 2	2 2 2	0.18 0.10 0.086	0.0039 0.0033 0.0052	0.16 0.089 0.069	-1.63 -1.89 -1.98	D D D	5 5 5
28	6p - (¹ S)10d	² P° - ² D	[1954.3] [1892.5] [1955.1]	21952.4 20261.6 21952.4	73122.2 73101.9 73101.9	4 2 4	6 4 4	0.13 0.090 0.018	0.011 0.0097 0.0011	0.29 0.12 0.027	-1.35 -1.71 -2.38	D D D	5 3 5
29	6p - (¹ S)11s	² P° - ² S	<u>1948.7</u> [1970.3] [1906.8]	<u>21388.8</u> 21952.4 20261.6	<u>72705.3</u> 72705.3 72705.3	6 4 2	2 2 2	0.12 0.067 0.051	0.0022 0.0019 0.0028	0.085 0.050 0.035	-1.88 -2.11 -2.26	D D D	5 5 5
30	6d - (¹ S)5f	² D - ² F° (5)	<u>8726.9</u> 8710.82 8737.74 [8897.5]	<u>46072.7</u> 46154.9 45949.5 46154.9	<u>57528.5</u> 57631.6 57390.9 57390.9	10 6 4 6	14 8 6 6	0.88 0.80 0.93 0.053	1.4 1.2 1.6 0.064	400 210 180 11	1.15 0.86 0.81 -0.42	D D D D	5 5 5 5
31	6d - (¹ S)6f	² D - ² F° (6)	<u>5380.3</u> 5391.60 5361.35 5421.05	<u>46072.7</u> 46154.9 45949.5 46154.9	<u>64653.9</u> 64697.1 64596.3 64596.3	10 6 4 6	14 8 6 6	0.051 0.052 0.048 0.0019	0.031 0.030 0.031 8.3x10 ⁻⁴	5.5 3.2 2.2 0.089	-0.51 -0.74 -0.91 -2.30	D D D D	5 5 5 5

No.	Transition Array	Multiplet	$\lambda(\text{\AA})$	$E_i(\text{cm}^{-1})$	$E_k(\text{cm}^{-1})$	g_i	g_k	$A_{ki}(10^8 \text{s}^{-1})$	f_{ik}	S(at.u.)	log gf	Accu.	L
32	6d - (¹ S)8p	² D - ² P°	[6457.7] [6373.2]	46154.9 45949.5	61636 61636	6 4	4 4	0.0030 6.7x10 ⁻⁴	0.0012 4.1x10 ⁻⁴	0.16 0.034	-2.13 -2.79	D D	5 5
33	6d - (¹ S)8f	² D - ² F°	[3842.8] [3816.7]	46154.9 45949.5	72170.2 72142.7	6 4	8 6	0.0022 0.0023	6.4x10 ⁻⁴ 7.5x10 ⁻⁴	0.048 0.037	-2.42 -2.53	D D	5 5
34	7s - (¹ S)7p	² S - ² P°	<u>13421</u> [13058] [14211]	42355.2 42355.2 42355.2	<u>49804.2</u> 50011.2 49390.1	2 2 2	6 4 2	0.20 0.21 0.18	1.6 1.1 0.53	140 94 50	0.51 0.34 0.03	D D D	5 5 5
35	7s - (¹ S)8p	² S - ² P°	[5185.1]	42355.2	61636	2	4	0.018	0.014	0.48	-1.55	D	5
36	7p - (¹ S)7d	² P° - ² D	<u>9944.6</u> [10115] [9603.3] [10213]	<u>49804.2</u> 50011.2 49390.1 50011.2	<u>59857.1</u> 59895.0 59800.3 59800.3	6 4 2 4	10 6 4 4	0.44 0.45 0.35 0.077	1.1 1.0 0.96 0.12	210 140 61 16	0.82 0.62 0.28 -0.32	D D D D	5 5 5 5
37	7p - (¹ S)8s	² P° - ² S	<u>12161</u> [12475] [11577]	<u>49804.2</u> 50011.2 49390.1	58025.2 58025.2 58025.2	6 4 2	2 2 2	0.44 0.31 0.13	0.33 0.36 0.27	79 59 20	0.29 0.16 -0.27	D D D	5 5 5
38	7p - (¹ S)8d	² P° - ² D (13)	<u>5915.3</u> 5981.25 5784.18 5999.85	<u>49804.2</u> 50011.2 49390.1 50011.2	<u>66704.8</u> 66725.4 66673.8 66673.8	6 4 2 4	10 6 4 4	0.19 0.16 0.20 0.026	0.16 0.13 0.20 0.014	19 10 7.6 1.1	-0.01 -0.29 -0.40 -1.26	D D D D	5 5 5 5
39	7p - (¹ S)9s	² P° - ² S (12)	<u>6295.8</u> 6378.91 6135.83	<u>49804.2</u> 50011.2 49390.1	65683.4 65683.4 65683.4	6 4 2	2 2 2	0.18 0.099 0.085	0.036 0.030 0.048	4.5 2.5 1.9	-0.66 -0.92 -1.02	D D D	5 5 5

No.	Transition Array	Multiplet	$\lambda(\text{\AA})$	$E_i(\text{cm}^{-1})$	$E_k(\text{cm}^{-1})$	g_i	g_k	$A_{ki}(10^8 \text{ s}^{-1})$	f_{ik}	S(at.u.)	log gf	Accu.	L
40	7p - (¹ S)9d	² P° - ² D (15)	<u>4798.3</u> 4843.46 4708.94 4850.84	<u>49804.2</u> 50011.2 49390.1 50011.2	<u>70639.3</u> 70651.9 70620.4 70620.4	6 4 2 4	10 6 4 4	0.10 0.093 0.097 0.014	0.058 0.049 0.065 0.0051	5.5 3.1 2.0 0.32	-0.46 -0.71 -0.89 -1.69	D D D D	5 5 5 5
41	7p - (¹ S)10s	² P° - ² S (14)	<u>4946.5</u> 4997.81 4847.14	<u>49804.2</u> 50011.2 49390.1	<u>70014.7</u> 70014.7 70014.7	6 4 2	2 2 2	0.10 0.061 0.041	0.012 0.012 0.014	1.2 0.76 0.46	-1.13 -1.34 -1.54	D D D	5 5 5
42	7p - (¹ S)10d	² P° - ² D (17)	<u>4288.8</u> 4325.73 4616.04 4329.62	<u>49804.2</u> 50011.2 49390.1 50011.2	<u>73114.1</u> 73122.2 73101.9 73101.9	6 4 2 4	10 6 4 4	0.062 0.059 0.048 0.0088	0.028 0.025 0.031 0.0025	2.4 1.4 0.93 0.14	-0.77 -1.00 -1.21 -2.01	D D D D	5 5 5 5
43	7p - (¹ S)11s	² P° - ² S (16)	<u>4365.4</u> 4405.23 4287.80	<u>49804.2</u> 50011.2 49390.1	<u>72705.3</u> 72705.3 72705.3	6 4 2	2 2 2	0.064 0.039 0.024	0.0061 0.0057 0.0068	0.52 0.33 0.19	-1.44 -1.64 -1.87	D D D	5 5 5
44	8p - (¹ S)8d	² P° - ² D	<u>19342</u> [19643] [18729] [19845]	<u>61536</u> 61636 61336 61636	<u>66704.8</u> 66725.4 66673.8 66673.8	6 4 2 4	10 6 4 4	0.13 0.13 0.11 0.022	1.2 1.1 1.2 0.13	470 290 140 34	0.87 0.65 0.37 -0.28	D D D D	5 5 5 5
45	8p - (¹ S)9d	² P° - ² D	<u>10982</u> [11089] [10768] [11127]	<u>61536</u> 61636 61336 61636	<u>70639.3</u> 70651.9 70620.4 70620.4	6 4 2 4	10 6 4 4	0.063 0.063 0.053 0.010	0.19 0.17 0.19 0.019	41 25 13 2.7	0.05 -0.16 -0.43 -1.13	D D D D	5 5 5 5

No.	Transition Array	Multiplet	$\lambda(\text{\AA})$	$E_i(\text{cm}^{-1})$	$E_k(\text{cm}^{-1})$	g_i	g_k	$A_{ki}(10^8 \text{s}^{-1})$	f_{ik}	$S(\text{at.u.})$	log gf	Accu.	L
46	8p - (¹ S)10s	² P° - ² S	<u>11791</u>	<u>61536</u>	70014.7	6	2	0.069	0.048	11	-0.54	D	5
			[11932]	61636	70014.7	4	2	0.045	0.048	7.6	-0.71	D	5
			[11519]	61336	70014.7	2	2	0.024	0.048	3.6	-1.02	D	5
47	8p - (¹ S)10d	² P° - ² D	<u>8634.6</u>	<u>61536</u>	<u>73114.1</u>	6	10	0.037	0.069	12	-0.38	D	5
			[8703.7]	61636	73122.2	4	6	0.037	0.063	7.3	-0.60	D	5
			[8496.8]	61336	73101.9	2	4	0.031	0.067	3.7	-0.88	D	5
			[8719.1]	61636	73101.9	4	4	0.0057	0.0066	0.75	-1.58	D	5
48	8p - (¹ S)11s	² P - ² S	<u>8950.6</u>	<u>61536</u>	72705.3	6	2	0.041	0.016	2.9	-1.01	D	5
			[9031.5]	61636	72705.3	4	2	0.027	0.016	1.9	-1.19	D	5
			[8793.2]	61336	72705.3	2	2	0.014	0.016	0.95	-1.48	D	5

NBS TECHNICAL PUBLICATIONS

PERIODICALS

JOURNAL OF RESEARCH reports National Bureau of Standards research and development in physics, mathematics, chemistry, and engineering. Comprehensive scientific papers give complete details of the work, including laboratory data, experimental procedures, and theoretical and mathematical analyses. Illustrated with photographs, drawings, and charts.

Published in three sections, available separately:

● Physics and Chemistry

Papers of interest primarily to scientists working in these fields. This section covers a broad range of physical and chemical research, with major emphasis on standards of physical measurement, fundamental constants, and properties of matter. Issued six times a year. Annual subscription: Domestic, \$6.00; foreign, \$7.25*.

● Mathematical Sciences

Studies and compilations designed mainly for the mathematician and theoretical physicist. Topics in mathematical statistics, theory of experiment design, numerical analysis, theoretical physics and chemistry, logical design and programming of computers and computer systems. Short numerical tables. Issued quarterly. Annual subscription: Domestic, \$2.25; foreign, \$2.75*.

● Engineering and Instrumentation

Reporting results of interest chiefly to the engineer and the applied scientist. This section includes many of the new developments in instrumentation resulting from the Bureau's work in physical measurement, data processing, and development of test methods. It will also cover some of the work in acoustics, applied mechanics, building research, and cryogenic engineering. Issued quarterly. Annual subscription: Domestic, \$2.75; foreign, \$3.50*.

TECHNICAL NEWS BULLETIN

The best single source of information concerning the Bureau's research, developmental, cooperative and publication activities, this monthly publication is designed for the industry-oriented individual whose daily work involves intimate contact with science and technology—for engineers, chemists, physicists, research managers, product-development managers, and company executives. Annual subscription: Domestic, \$3.00; foreign, \$4.00*.

*Difference in price is due to extra cost of foreign mailing.

Order NBS publications from:

Superintendent of Documents
Government Printing Office
Washington, D.C. 20402

NONPERIODICALS

Applied Mathematics Series. Mathematical tables, manuals, and studies.

Building Science Series. Research results, test methods, and performance criteria of building materials, components, systems, and structures.

Handbooks. Recommended codes of engineering and industrial practice (including safety codes) developed in cooperation with interested industries, professional organizations, and regulatory bodies.

Special Publications. Proceedings of NBS conferences, bibliographies, annual reports, wall charts, pamphlets, etc.

Monographs. Major contributions to the technical literature on various subjects related to the Bureau's scientific and technical activities.

National Standard Reference Data Series. NSRDS provides quantitative data on the physical and chemical properties of materials, compiled from the world's literature and critically evaluated.

Product Standards. Provide requirements for sizes, types, quality and methods for testing various industrial products. These standards are developed cooperatively with interested Government and industry groups and provide the basis for common understanding of product characteristics for both buyers and sellers. Their use is voluntary.

Technical Notes. This series consists of communications and reports (covering both other agency and NBS-sponsored work) of limited or transitory interest.

Federal Information Processing Standards Publications. This series is the official publication within the Federal Government for information on standards adopted and promulgated under the Public Law 89-306, and Bureau of the Budget Circular A-86 entitled, Standardization of Data Elements and Codes in Data Systems.

CLEARINGHOUSE

The Clearinghouse for Federal Scientific and Technical Information, operated by NBS, supplies unclassified information related to Government-generated science and technology in defense, space, atomic energy, and other national programs. For further information on Clearinghouse services, write:

Clearinghouse
U.S. Department of Commerce
Springfield, Virginia 22151

U.S. DEPARTMENT OF COMMERCE
WASHINGTON, D.C. 20230

POSTAGE AND FEES PAID
U.S. DEPARTMENT OF COMMERCE

OFFICIAL BUSINESS
